



FROTH-PAK (TM) 600 B 25FS NCFC Polyurethane Spray Foam System
MATERIAL SAFETY DATA SHEET

1) PRODUCT AND COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
Midland Michigan 48674
USA

24-Hour Emergency Phone Number: 989-636-4400

Customer Service: 800-366-4740

PRODUCT NAME : FROTH-PAK (TM) 600 B 25FS NCFC Polyurethane Spray Foam System

MATERIAL TYPE : Polyol blend

ISSUE DATE : 07/19/2007

REVISION DATE : 03/10/2006

2) COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	%
Polyols	Mixture	30-60%
Diethylene Glycol	111-46-6	1-5%
Triethyl Phosphate	78-40-0	1-5%
Flame Retardants	Mixture	5-10%
1,1,1,3,3-Pentafluoropropane	460-73-1	7-13%
1,1,1,2-Tetrafluoroethane	811-97-2	10-30%

3) HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION! Contents under pressure.

Vapors reduce oxygen available for breathing and are heavier than air.

May cause slight temporary eye irritation. May cause skin irritation if skin is abraded. When heated, may cause thermal burns and heated mist may cause respiratory irritation. Avoid contact with strong acids and oxidizers and un-intended contact with isocyanates.

EYE

May cause slight temporary eye irritation.

SKIN

Prolonged or repeated exposure not likely to cause significant skin irritation. May cause more severe response if skin is abraded, scratched or cut. A single prolonged exposure is not likely to result in the material being absorbed through the skin in harmful amounts. Material may be handled at elevated temperatures; contact with heated material may cause thermal burns.

INGESTION

Single dose oral toxicity is considered to be low. Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause injury.

INHALATION

Exposure to fluorocarbons at high concentrations may effect the nervous system and produce a rapid anesthetic effect. The dense vapor of this material can reduce the oxygen available for breathing and produce symptoms such as headache, dizziness, drowsiness, cyanosis and lack of muscle control followed by collapse. Prolonged exposure to an oxygen-deficient atmosphere may be fatal. Inhalation of this material may cause an increase in the sensitivity of the heart to adrenaline, which could result in irregular heart beats and reduced heart function.

At room temperatures, vapors are minimal due to physical properties; a single exposure

FROTH-PAK (TM) 600 B 25FS NCFC Polyurethane Spray Foam System

MATERIAL SAFETY DATA SHEET

is not likely to be hazardous. If material is heated or mist is produced, concentrations may be attained that are sufficient to cause respiratory irritation.

SYSTEMIC EFFECTS

Excessive exposure to fluorocarbons may effect the central nervous system and produce anesthetic and narcotic-like symptoms.

4) FIRST-AID MEASURES

EYE

Immediately flush eyes with plenty of water. Remove contacts after first few minutes and continue washing.

SKIN

Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists.

INGESTION

If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

INHALATION

Remove to fresh air if effects occur. Consult a Physician.

NOTE TO PHYSICIAN

No specific antidote. Supportive care. Treatment based on judgment of the physician in response to reactions of the patient.

5) FIRE-FIGHTING MEASURES

HAZARDOUS COMBUSTION PRODUCTS

Incomplete combustion may lead to the build-up of toxic pyrolysis products. Complete combustion will result in: Carbon oxides, Nitrogen oxides, Water, Ammonia and trace amounts of Hydrogen Cyanide.

Additional combustion products may include hydrogen fluoride, hydrogen chloride and chlorine.

Additional combustion products may include hydrogen bromide and/or bromine.

OTHER FLAMMABILITY INFORMATION

Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Spills of these organic liquids on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. Burning liquids may be extinguished by dilution with water. Do not use direct water stream, it may spread fire.

EXTINGUISHING MEDIA

Use carbon dioxide, dry chemical, foam, water fog or fine spray. Alcohol resistant foams (ATC type) are preferred if available. General purpose synthetic foams (including AFFF) or protein foams may function, but much less effective. Do not use direct water stream which can spread fire.

FIRE FIGHTING INSTRUCTIONS

Keep people away. Isolate fire area and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water is not recommended but may be applied in very large quantities as a fine spray when other extinguishing agents are not available. Contain fire water run-off if possible. Do not use direct water stream. May spread fire. Fight fire from protected location or safe distance. Consider use of unmanned hose holder or monitor nozzles. Use water spray to cool fire exposed containers and fire affected zone until fire is out. Immediately withdraw all personnel from area in case of rising sound from venting safety devices or

FROTH-PAK (TM) 600 B 25FS NCFC Polyurethane Spray Foam System
MATERIAL SAFETY DATA SHEET

discoloration of the containers. Move containers from fire area if this is possible without hazard.

PROTECTIVE EQUIPMENT - FIRE FIGHTERS

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, pants, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6) ACCIDENTAL RELEASE MEASURES

PROTECT PEOPLE

Isolate area. May be a slipping hazard. Wear adequate personal protective equipment

PROTECT THE ENVIRONMENT

Contain material to prevent contamination of ground and surface water. Spills should be collected to prevent contamination of waterways. Recover if possible, or dispose of according to applicable regulations.

CLEAN-UP

Spills should be contained by, and covered with large quantities of sand, earth or any other readily available absorbent material, which is then brushed in vigorously to assist absorption. The mixture can then be collected into drums and removed for disposal. Wash residues from area with soap and water and rinse down. Contaminated water should be retained, not being allowed to flow into ground or surface water.

7) HANDLING AND STORAGE

HANDLING

CAUTION: Contents under pressure. Avoid open flames. Do not puncture or incinerate.

Avoid contact of this product with water at all times during handling and storage. Use only with adequate ventilation. Keep equipment clean. Use disposable containers and tools where possible. Do not eat, drink, or smoke in working area.

STORAGE

Store in a dry place between 75F-105F (24C-41C). Keep containers tightly closed when not in use. Protect from atmospheric moisture. Maintain a nitrogen atmosphere. Do not store product contaminated with water to prevent potentially hazardous reaction.

8) EXPOSURE CONTROL/PERSONAL PROTECTION

ENGINEERING CONTROLS

Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

EYE/FACE PROTECTION

Use chemical goggles. If vapor exposure causes eye discomfort, use a full-face respirator. Eye wash fountain should be located in immediate work area.

SKIN PROTECTION

Use gloves impervious to this material. Wear clean, long-sleeved, body covering clothing. After work and before eating, drinking or smoking wash and clean yourself carefully with soap and water. Contaminated clothing should be washed and/or dry cleaned before re-use.

RESPIRATORY PROTECTION

For most conditions, no respiratory protection is needed; however, if handling at elevated temperature without sufficient ventilation or in presence of aerosols, use an approved air-purifying respirator. Atmospheric levels should be maintained below the exposure guideline.

EXPOSURE GUIDELINES(S)

FROTH-PAK (TM) 600 B 25FS NCFC Polyurethane Spray Foam System

MATERIAL SAFETY DATA SHEET

1,1,1,3,3 pentafluoropropane: 300 ppm TWA set by manufacturer.

Diethylene glycol: 10 mg/m³ TWA8 AIHA WEEL and Interim IHG (aerosol)

50 ppm TWA8 Interim IHG (aerosol and vapor)

9) PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE

liquid

SOLUBILITY IN WATER

not determined

SPECIFIC GRAVITY

not determined

10) STABILITY AND REACTIVITY

CHEMICAL STABILITY

Stable under recommended storage conditions.

CONDITIONS TO AVOID

Product can oxidize or decompose at elevated temperatures.

INCOMPATIBILITY WITH OTHER MATERIALS

Avoid contact with oxidizing materials and strong acids. Avoid unintended contact with isocyanates. The reaction of polyols and isocyanates generates heat.

HAZARDOUS DECOMPOSITION PRODUCTS

None under normal conditions of storage and use.

HAZARDOUS POLYMERIZATION

Will not occur by itself.

11) TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

Assesments may be based on studies of the individual components or on families of chemicals.

ACUTE

Inhalation LD50 for diethylene glycol is >4.4 mg/l for 4 hours (rat).

Excessive exposure to 1,1,1,2-tetrafluoroethane may cause irritation to upper respiratory tract (nose and throat). Acute inhalation toxicity of 1,1,1,2-tetrafluoroethane is low, but exposure to high concentrations causes asphyxiation.

1,1,1,3,3-pentafluoropropane: acute inhalation LC50 in rats >200,000 ppm (4 hours). No lethality at 200,000 ppm. Evidence of transient anesthetic effect. Acute inhalation in mice >100,000 ppm (4 hours). No lethality at 100,000 ppm; evidence of transient underactivity during exposure.

SKIN

Polyol: LD50 in rabbits is >2000 mg/kg.

LD50 for diethylene glycol is 12510 mg/kg (rabbit).

1,1,1,3,3-pentafluoropropane Dermal LD50 in rabbits >2000 mg/kg.

INGESTION

Polyol: LD50 in rats is >2000 mg/kg.

Human lethal dose of diethylene glycol is approx. 2 ounces (65 ml) (1/4 cup).

LD50 for diethylene glycol is 25244 mg/kg (rat).

12) ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION

The stratosphere ozone depletion potential (ODP) of 1,1,1,2-tetrafluoroethane, relative to CFC-11 and CFC-12 (ODP=1) is 0.

MOVEMENT & PARTITIONING

No bioconcentration of the polyol is expected.

1,1,1,2-tetrafluoroethane volatilization from water to air is expected.

DEGRADATION & PERSISTENCE

Proprietary flame retardant is persistent in the environment.

Based on information for 1,1,1,2-tetrafluoroethane: material is expected to be very stable in the environment. Because of low biodegradability, the product should be prevented from reaching water or soil.

ECOTOXICITY

Fire retardant: Avoid releasing to the environment. The LC50 for a structurally similar compound in Gluegill Sunfish (96H) = 12 mg/L (NOEC <10 mg/L).

13) DISPOSAL CONSIDERATIONS

DISPOSAL

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal methods must be in compliance with all Federal, State/Provincial and local laws and regulations.

Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. THE DOW CHEMICAL COMPANY HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION 2 (Composition/Information On Ingredients).

FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: recycler, reclaimer, incinerator or other thermal destruction device.

As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Center at 800-258-2436 or 989-832-1556 for further details.

14) TRANSPORT INFORMATION

US D.O.T.

This product is not regulated when pressures are less than 40 psi. When greater than 40 psi, the classification is: Compressed Gases, N.O.S. (Pentafluoropropane, Tetrafluoroethane), 2.2 UN1956.

CANADIAN TDG

This product is not regulated when pressures are less than 40 psi. When greater than 40 psi, the classification is: Compressed Gases, N.O.S. (Pentafluoropropane, Tetrafluoroethane), 2.2 UN1956.

15) REGULATORY INFORMATION

FROTH-PAK (TM) 600 B 25FS NCFC Polyurethane Spray Foam System
MATERIAL SAFETY DATA SHEET

NOTICE

The information herein is presented in good faith and believed to be accurate as of the effective date shown above. However, no warranty, expressed or implied is given. Regulatory requirements are subject to change and may differ from one location to another; it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The following specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations. See other sections for health and safety information.

REGULATORY INFORMATION

U.S. REGULATIONS

SARA 313 INFORMATION: This product contains the following subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME CAS NUMBER

None

SARA HAZARD CATEGORY: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

An immediate health hazard

A delayed health hazard

TOXIC SUBSTANCES CONTROL ACT (TSCA):

All ingredients are on the TSCA inventory.

CALIFORNIA Prop 65: This product contains the following chemicals known to the State of California to cause cancer or other reproductive harm:

Residual 1,4 dioxane, CAS# 123-91-1 amount: <0.500 ppm in diethylene glycol

Residual Ethylene glycol monomethyl ether, CAS# 109-86-4 amount: <0.050ppm in diethylene glycol

Flame retardant

PENNSYLVANIA STATE RIGHT TO KNOW Hazardous or Environmental Hazardous Substance:

Diethylene glycol CAS: 111-46-6 Amount: 1-5%

Residual Ethylene glycol monomethyl ether CAS # 109-86-4 amount: <0.050 ppm in diethylene glycol

OSHA HAZARD COMMUNICATION STANDARD:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

COMPREHENSIVE ENVIRONMENTAL RESPONSE COMPENSATION AND LIABILITY ACT (CERCLA, or SUPERFUND):

This product contains the following substance(s) listed as "Hazardous Substances"

FROTH-PAK (TM) 600 B 25FS NCFC Polyurethane Spray Foam System
MATERIAL SAFETY DATA SHEET

under CERCLA which may require reporting of releases:

Category:

Chemical Name CAS# RQ

NONE

CANADIAN REGULATIONS

WHMIS INFORMATION: The Canadian Workplace Hazardous Materials Information System (WHMIS) Classification for this product is:

D2B - eye or skin irritant

Refer elsewhere in the MSDS for specific warnings and safe handling information. Refer to the employer's workplace education program.

CPR STATEMENT: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

HAZARDOUS PRODUCTS ACT INFORMATION: This product contains the following ingredients which are Controlled Products and/or on the Ingredient Disclosure List (Canadian HPA section 13 and 14):

COMPONENTS: CAS #

Triethyl Phosphate 78-40-0

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA):

This product contains some substances NOT listed on the Canadian Domestic Substances List (DSL).

16) OTHER INFORMATION

OTHER INFORMATION

EPA intends to promulgate a SNUR (Significant New Use Rule) restricting the use of 1,1,1,3,3 pentafluoropropane. Use as a blowing agent is one of the approved uses.

The Canadian EPA has imposed Managerial Condition 12088 upon the use of 1,1,1,3,3 pentafluoropropane. These conditions must be met before the product can be ordered and used in Canada.

No other information.

(TM), *, or (R) Indicates a trademark of The Dow Chemical Company.