



# Material Safety Data Sheet

The Dow Chemical Company

**Product Name:** FROTH-PAK(TM) 400 AF HFC Polyurethane Foam System      **Issue Date:** 05/22/2008

**Print Date:** 25 Jul 2008

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## 1. Product and Company Identification

### Product Name

FROTH-PAK(TM) 400 AF HFC Polyurethane Foam System

### COMPANY IDENTIFICATION

The Dow Chemical Company  
2030 Willard H. Dow Center  
Midland, MI 48674  
USA

Customer Information Number: 800-258-2436

### EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 989-636-4400

**Local Emergency Contact:** 989-636-4400

## 2. Hazards Identification

### Emergency Overview

**Color:** Brown

**Physical State:** Liquid

**Odor:** Musty

### Hazards of product:

**WARNING!** May cause eye irritation. May cause skin irritation. May cause allergic skin reaction. May cause allergic respiratory reaction. Vapor reduces oxygen available for breathing. May cause central nervous system effects. Keep upwind of spill. May cause anesthetic effects. May cause respiratory tract irritation. May cause lung injury. May react with water. Stay out of low areas. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction. Toxic fumes may be released in fire situations. Contents under pressure. Avoid temperatures above 41 °C (106 °F). Avoid temperatures below 20 °C (68 °F).

### OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Potential Health Effects

**Eye Contact:** May cause moderate eye irritation. May cause slight temporary corneal injury.

**Skin Contact:** Prolonged contact may cause skin irritation with local redness. May stain skin.

**Skin Absorption:** Prolonged skin contact is unlikely to result in absorption of harmful amounts.

**Skin Sensitization:** Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

**Inhalation:** In confined or poorly ventilated areas, vapor can easily accumulate and can cause unconsciousness and death due to displacement of oxygen. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. Decreased lung function has been associated with overexposure to isocyanates. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). May cause central nervous system effects. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

**Respiratory Sensitization:** May cause allergic respiratory response. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

**Ingestion:** Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Observations in animals include: Gastrointestinal irritation.

**Effects of Repeated Exposure:** Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

**Cancer Information:** Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m<sup>3</sup>) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

**Birth Defects/Developmental Effects:** In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother. Based on information for component(s): 1,1,1,2-Tetrafluoroethane. Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

---

---

## 3. Composition Information

---

---

Component	CAS #	Amount
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	>= 60.0 - <= 100.0 %
4,4' -Methylenediphenyl diisocyanate	101-68-8	30.0 - 60.0 %
1,1,1,2-Tetrafluoroethane	811-97-2	>= 5.0 - <= 10.0 %

Note: CAS 101-68-8 is an MDI isomer that is part of CAS 9016-87-9.

---

---

## 4. First-aid measures

---

---

**Eye Contact:** Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist.

**Skin Contact:** Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. An MDI skin decontamination study demonstrated that cleaning very soon after exposure is important, and that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Ingestion:** If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

**Notes to Physician:** Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

**Medical Conditions Aggravated by Exposure:** Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

---

---

## 5. Fire Fighting Measures

---

---

**Extinguishing Media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water is not recommended, but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out.

**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

**Unusual Fire and Explosion Hazards:** Product reacts with water. Reaction may produce heat and/or gases. This reaction may be violent. Container may rupture from gas generation in a fire situation. Vaporizes quickly at room temperature. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Dense smoke is emitted when burned without sufficient oxygen.

**Hazardous Combustion Products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Isocyanates. Hydrogen fluoride. Hydrogen cyanide. Carbon monoxide. Carbon dioxide.

---

---

## 6. Accidental Release Measures

---

---

**Steps to be Taken if Material is Released or Spilled:** Contain spilled material if possible. Absorb with materials such as: Sawdust. Vermiculite. Dirt. Sand. Clay. Cob grit. Milsorb®. Do NOT use absorbent materials such as: Cement powder (Note: may generate heat). Collect in suitable and properly labeled open containers. Do not place in sealed containers. Suitable containers include: Metal drums. Plastic drums. Polylined fiber pacs. Wash the spill site with large quantities of water. Attempt to neutralize by adding suitable decontaminant solution: Formulation 1: sodium carbonate 5 - 10%; liquid detergent 0.2 - 2%; water to make up to 100%, OR Formulation 2: concentrated ammonia solution 3 - 8%; liquid detergent 0.2 - 2%; water to make up to 100%. If ammonia is used, use good ventilation to prevent vapor exposure. Contact Dow for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

**Personal Precautions:** Isolate area. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. Keep unnecessary and unprotected personnel from entering the area. If

available, use foam to smother or suppress. Refer to Section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. See Section 10 for more specific information.

**Environmental Precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

## 7. Handling and Storage

### Handling

**General Handling:** Avoid breathing vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Use with adequate ventilation. Wash thoroughly after handling. Keep container tightly closed. Contents under pressure. Do not puncture or incinerate container. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Do not enter confined spaces unless adequately ventilated. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

### Storage

Store under cover in a dry, clean, cool, well ventilated place away from sunlight. Do not store product contaminated with water to prevent potential hazardous reaction.

**Storage Period:** 6 Months                      **Storage temperature:** 15 - 27 °C

## 8. Exposure Controls / Personal Protection

### Exposure Limits

Component	List	Type	Value
4,4' -Methylenediphenyl diisocyanate	ACGIH	TWA	0.005 ppm
	OSHA Table Z-1	Ceiling	0.2 mg/m3 0.02 ppm
1,1,1,2-Tetrafluoroethane	WEEL	TWA	4,240 mg/m3 1,000 ppm

### Personal Protection

**Eye/Face Protection:** Use chemical goggles. Eye wash fountain should be located in immediate work area.

**Skin Protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task. Remove contaminated clothing immediately, wash skin area with soap and water, and launder clothing before reuse or dispose of properly. Items which cannot be decontaminated, such as shoes, belts and watchbands, should be removed and disposed of properly.

**Hand protection:** Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene. Chlorinated polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Viton. Neoprene. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). Nitrile/butadiene rubber ("nitrile" or "NBR"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Respiratory Protection:** Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved air-purifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure

air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

**Ingestion:** Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

### Engineering Controls

**Ventilation:** Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure.

---

---

## 9. Physical and Chemical Properties

---

---

<b>Physical State</b>	Liquid
<b>Color</b>	Brown
<b>Odor</b>	Musty
<b>Flash Point - Closed Cup</b>	Not applicable, Gas
<b>Flammable Limits In Air</b>	<b>Lower:</b> No test data available <b>Upper:</b>
<b>Autoignition Temperature</b>	No test data available
<b>Vapor Pressure</b>	225 psi @ 54 °C Container is under pressure.
<b>Boiling Point (760 mmHg)</b>	<i>No test data available .</i>
<b>Vapor Density (air = 1)</b>	No test data available
<b>Specific Gravity (H2O = 1)</b>	1.02 - 1.04 25 °C/25 °C <i>ASTM D891</i>
<b>Freezing Point</b>	No test data available
<b>Melting Point</b>	No test data available
<b>Solubility in Water (by weight)</b>	insoluble, reacts, evolution of CO2
<b>pH</b>	<i>Not applicable</i>
<b>Kinematic Viscosity</b>	No test data available

---

---

## 10. Stability and Reactivity

---

---

### Stability/Instability

Stable under recommended storage conditions. See Storage, Section 7.

**Conditions to Avoid:** Avoid temperatures above 41 °C (106 °F). Avoid temperatures below 20 °C (68 °F). Elevated temperatures can cause container to vent and/or rupture. Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid. Avoid moisture. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction.

**Incompatible Materials:** Avoid contact with: Acids. Alcohols. Amines. Ammonia. Bases. Metal compounds. Strong oxidizers. Diisocyanates react with many materials and the rate of reaction increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the diisocyanate. Diisocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Reaction with water will generate carbon dioxide and heat. Avoid unintended contact with polyols. The reaction of polyols and isocyanates generate heat.

### Hazardous Polymerization

Can occur.

### **Thermal Decomposition**

Decomposition products depend upon temperature, air supply and the presence of other materials. Toxic gases are released during decomposition.

---

---

## **11. Toxicological Information**

---

---

### **Acute Toxicity**

#### **Ingestion**

Single dose oral LD50 has not been determined. Estimated LD50, Rat > 10,000 mg/kg

#### **Skin Absorption**

The dermal LD50 has not been determined. Estimated LD50, Rabbit > 2,000 mg/kg

#### **Inhalation**

The LC50 has not been determined. Estimated LC50, Aerosol, Rat > 490 mg/m3

### **Sensitization**

#### **Skin**

Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

#### **Respiratory**

May cause allergic respiratory response. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

### **Repeated Dose Toxicity**

Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

### **Chronic Toxicity and Carcinogenicity**

Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m3) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

### **Developmental Toxicity**

In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother. Based on information for component(s): 1,1,1,2-Tetrafluoroethane. Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

### **Genetic Toxicology**

Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.

---

---

## **12. Ecological Information**

---

---

### **ENVIRONMENTAL FATE**

Data for Component: **Diphenylmethane Diisocyanate, isomers and homologues**

#### **Movement & Partitioning**

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

#### **Persistence and Degradability**

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Data for Component: 4,4' -Methylenediphenyl diisocyanate

**Movement & Partitioning**

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

**Persistence and Degradability**

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

Data for Component: 1,1,1,2-Tetrafluoroethane

**Movement & Partitioning**

Bioconcentration potential is low (BCF less than 100 or log Pow less than 3). Potential for mobility in soil is high (Koc between 50 and 150).

**Henry's Law Constant (H):** 5.00E-2 atm\*m3/mole; 25 °C Measured

**Partition coefficient, n-octanol/water (log Pow):** 1.68 Estimated

**Partition coefficient, soil organic carbon/water (Koc):** 97 Estimated

**Persistence and Degradability**

1,1,1,2-Tetrafluoroethane (HFC-134a) has a stratospheric ozone depletion potential (ODP) of zero, relative to CFC 12 (ODP=1). Material is expected to biodegrade only very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

**Indirect Photodegradation with OH Radicals**

Rate Constant	Atmospheric Half-life	Method
6.20E-15 cm3/s	1,700 d	Estimated

**OECD Biodegradation Tests:**

Biodegradation	Exposure Time	Method
4 %	28 d	OECD 301D Test

**Theoretical Oxygen Demand:** 0.47 mg/mg

**ECOTOXICITY**

Data for Component: Diphenylmethane Diisocyanate, isomers and homologues

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

**Toxicity to Soil Dwelling Organisms**

LC50, Earthworm Eisenia foetida, adult, 14 d: > 1,000 mg/kg

Data for Component: 4,4' -Methylenediphenyl diisocyanate

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species. Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

**Toxicity to Soil Dwelling Organisms**

LC50, Earthworm Eisenia foetida, adult, 14 d: > 1,000 mg/kg

Data for Component: 1,1,1,2-Tetrafluoroethane

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

**Fish Acute & Prolonged Toxicity**

LC50, rainbow trout (Oncorhynchus mykiss), static, 96 h: 450 mg/l

**Aquatic Invertebrate Acute Toxicity**

EC50, water flea Daphnia magna, 48 h, immobilization: 980 mg/l

## 13. Disposal Considerations

---

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. As a service to its customers, Dow can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Dow's Customer Information Group at 1-800-258-2436 or 1-989-832-1556 (U.S.), or 1-800-331-6451 (Canada) for further details.

## 14. Transport Information

---

### DOT Non-Bulk

**Proper Shipping Name:** COMPRESSED GAS, N.O.S.

**Technical Name:** Fluorinated Hydrocarbons, Nitrogen

**Hazard Class:** 2.2    **ID Number:** UN1956

### DOT Bulk

**Proper Shipping Name:** COMPRESSED GAS, N.O.S.

**Technical Name:** Fluorinated Hydrocarbons, Nitrogen

**Hazard Class:** 2.2    **ID Number:** UN1956

### IMDG

**Proper Shipping Name:** COMPRESSED GAS, N.O.S.

**Technical Name:** Fluorinated Hydrocarbons, Nitrogen

**Hazard Class:** 2.2    **ID Number:** UN1956

**EMS Number:** F-C,S-V

**Marine pollutant.:** No

### ICAO/IATA

**Proper Shipping Name:** COMPRESSED GAS, N.O.S.

**Technical Name:** Fluorinated Hydrocarbons, Nitrogen

**Hazard Class:** 2.2    **ID Number:** UN1956 **Cargo Packing Instruction:** 200

**Passenger Packing Instruction:** 200

### Additional Information

Reportable quantity: 5,556 lb – MDI

*This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.*

## 15. Regulatory Information

---

**OSHA Hazard Communication Standard**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312**

<b>Immediate (Acute) Health Hazard</b>	Yes
<b>Delayed (Chronic) Health Hazard</b>	Yes
<b>Fire Hazard</b>	No
<b>Reactive Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	Yes

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

This product contains the following substances which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372.

<b>Component</b>	<b>CAS #</b>	<b>Amount</b>
4,4' -Methylenediphenyl diisocyanate	101-68-8	>= 30.0 - <= 60.0 %
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	>= 60.0 - <= 100.0 %

**Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:**

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

<b>Component</b>	<b>CAS #</b>	<b>Amount</b>
4,4' -Methylenediphenyl diisocyanate	101-68-8	>= 30.0 - <= 60.0 %

**Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:**

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

**California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)**

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

**US. Toxic Substances Control Act**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

**CEPA - Domestic Substances List (DSL)**

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

---

---

**16. Other Information**

---

---

**Recommended Uses and Restrictions**

Component(s) for the manufacture of urethane polymers.

**Revision**

Identification Number: 64144 / 1001 / Issue Date 05/22/2008 / Version: 3.1

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

N/A	Not available
W/W	Weight/Weight

OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

*The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.*